

F-HYD 400 SERIES

Food Grade Synthetic Hydraulic Oil

F-HYD 400 is based on synthetic oils, making the oil tasteless and odourless. The product is not aggressive to hoses, seals or gaskets, giving an elongated lifetime to both the oil and the machine. F-HYD 400 is completely resistant to foaming and has an excellent air release ability. The product is developed to withstand large variations in temperatures, has excellent water resistance and give good protection and prevention of corrosion.

Environmentally adapted Food grade quality Wide application range Applications

Hydraulic systems Freezing house Food industry Automotive industry etc

TECHNICAL DATA

| | ISO grade | 15 | 46 |
|---|-----------|-------------|-------------|
| | | F HYD 401 | F HYD 404 |
| Colour | | Transparent | Transparent |
| Viscosity at 40 °C, mm ² /s | ISO 3104 | 15 | 46 |
| Viscosity at 100 °C, mm ² /s | ISO 3104 | 3.77 | 7.96 |
| Viscosity index | ISO 2909 | >140 | >140 |
| Pour Point, °C | ISO 3016 | -69 | -57 |
| Flash Point, °C | ISO 2592 | >150 | >180 |

MPI approved C15 (All animal product except dairy)

Imported and Distributed by Oil Imports Ltd, 56 Whakatu Road, Whakatu, Hastings, 4172.

Phone: 06 871 5325, Fax: 06 870 4890, www.totaloilsolutions.co.nz.

Oil Imports Ltd. is the authorised dealer of Cargo products in New Zealand.