

**International Specifications** JASO M315-1A

**Manufacturers Approvals** Meets the requirement of :  
AISIN WARNER JWS 3324  
HONDA DW-1  
HYUNDAI NWS-9638 T-5, SP-IV, SP-IV-RR, SPH-IV  
TOYOTA TYPE WS

Suitable for :

BENTLEY P/N PY112995PA

BMW P/N 83 22 0 142 516, 83 22 0 397 114, 83 22 2 163 514, 83 22 2 289 720, 83 22 2 305 397

CHRYSLER P/N 05127382AA, 68043742AA

FORD MERCON® LV, FORD MERCON® SP

FORD P/N XT-10-QLV, XT-6-QSP, XT-6-DSP

GM DEXRON® VI

GM P/N 88863400, 88863401, 12378515

HYUNDAI P/N 040000C90SG

JAGUAR LAND ROVER P/N TYK500050

MASERATI P/N 231603

MB-236.12, MB-236.14, MB-236.41

PORSCHE P/N 000 043 304 00

SAAB P/N 93 165 147

VW G 052 533, G 055 005-A, G 055 005-A2, G 055 540-A2

\* Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

## 1 - Applications

ELFMATIC LV MV is an innovative automatic transmission fluid based on an advanced synthetic technology allowing very high performances. Offers fuel economies thanks to low viscosity.

ELFMATIC LV MV has been developed to meet the needs of modern transmission where higher efficiency is required. It is a low viscosity formulation that meets the more demanded OEM specifications.

## 2 - Customer Benefits

Formulated with selected viscosity modifiers which provide excellent friction characteristics. These improve driver's comfort with smooth and efficient shifting without shudder.

High-quality transmission fluid that offers extended life, fuel economy benefits, excellent lubrication, and protection for transmissions.

It provides oxidation resistance and foaming control for optimal performance in various driving conditions.

## 3 - Characteristics

TEST	TEST METHOD	UNITS	VALUE
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	845
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	30.28
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.05
Viscosity index	ASTM D2270	-	156
Pour point	ASTM D97	°C	-45
Flash point	ASTM D92	°C	208
TBN	ASTM D2896	mgKOH/g	-
Sulphated Ash	ASTM D874	% m/m	-

\* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

## 4 - Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## 5 - Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The Safety Data Sheet can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.