

# **Technical Data sheet**

#### & Chain O i

## Biodegradable Chain and Cutter Bar Lubricant

## **Description**

Bar & Chain Oil 150 is a naturally tacky, rapeseed oil based, readily biodegradable lubricant providing a superior level of lubricity and improved anti-corrosion & anti-wear protection. It contains specially selected EP/Extreme Pressure and AW/Anti-Wear additives and naturally present extremely high Viscosity Index. Developed to replace the usual mineral oil based chain lubricants in order to provide a greater performance and reduce environmental footprint.

## **Areas of Application**

Designed for the lubrication of stationery power saws and cutting equipment. Recommended lubricant for industrial and domestic applications where a contact between equipment and the surrounding natural environment is inevitable. Enhanced lubricity and improved tackiness define it particularly suitable for use on hot summer days.

#### **Characteristic features**

- Excellent lubricating properties far superior than that of mineral oils
- Naturally greater adhesion than mineral oils
- Protected against polymerization
- Improved anti-corrosion & anti-wear protection
- Increased overall system efficiency
- Positive impact on CO<sub>2</sub> emissions
- Ideal for use all year around
- Readily biodegradable Over 98% Biodegradability within 21 days
- **EU Ecolabel Certificate of environmental excellence**



CZ / 27 / 001

### **TYPICAL CHARACTERISTICS**

PARAMETER	UNIT	TEST METHOD	VALUE
Density at 15 °C	kg/m³	ISO 12185	940
Kinematic Viscosity at 40°C	mm²/s	ASTM D445	150
Viscosity Index (VI)			>200
Pour point	°C	ASTM D97	-30
Flash point, COC	°C	ASTM D92	>280
Steel corrosion at 100°C/3h			negative
Biodegradability (within 21 days)	%	OECD 301B	>98

Issue Date: 30/01/2019

**Pacific Bio Lubricants Limited** 11H Piermark Dr., North Harbour

Auckland 0632, New Zealand Postal: PO Box 35085, Auckland 0753 **Sales and Technical Support** 

Phone: +64 9 973 4390 NZ Freephone: 0800 582 326 Email: info@lubeco.co.nz

