



PROSYLVA CHAIN EXTREM PLUS



Loss lubrication of chainsaw and high-speed machinery

APPLICATIONS

TOTAL PROSYLVA CHAIN EXTREM PLUS is dedicated for all **high-speed machineries**: manual or mechanical chainsaw, chain conveyors. This lubricant is adapted to **all wood transformation**.

This product is particularly recommended for **manual chainsaw** of woodcutter and for industrial conveyors.

PERFORMANCES AND CUSTOMER BENEFITS

TOTAL PROSYLVA CHAIN EXTREM PLUS has a high **adhesive behaviour** which reduces spattering and guarantees the lubrication on the entire length of the moving chain.

TOTAL PROSYLVA CHAIN EXTREM PLUS exhibits the following **properties**:

- ✓ Reinforced anti-wear additivation
- ✓ Improved anti-rust property
- ✓ Friction reduction
- ✓ Chain and guide wear reduction
- ✓ Spattering, pollution and oil consumption reductions

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL PROSYLVA CHAIN EXTREM PLUS		Method	Value
Density at 15°C	kg/m ³	ASTM D1298	877
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	220
Pour Point	°C	ASTM D97	-21
TAC Level	%		5

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

TOTAL LUBRIFIANTS
562, avenue du Parc de l'Île
92029 Nanterre cedex
FRANCE

**TOTAL PROSYLVA
CHAIN EXTREM PLUS**
Update 11/2015
www.lubricants.total.com



This lubricant does not cause adverse health effects when used in the intended application.
A safety datasheet is accessible on request from your local dealer or on the website www.quickfds.com