

F-SPRAY 252

**Dry Release Agent and Lubricant**

F-SPRAY 252 is a lubricating and release agent, for instance, in packaging and process equipment. Prevents blockage and production stand-still on spindles, slideways and guides. Dries quickly and leaves a surface that is not oily or fatty. Wide application temperature range.

Prevents car doors, locks and rubber linings ability to stick/ freeze/scorch. Protects accumulator terminals, tools, weapons, sky lights, aluminium windows, etc from rust and corrosion.

**Directions for use:**

- Shake can well before use
- Avoid applying or spillage on floor and shoe soles – risk for slipping!

Properties	Applications
Fast drying	Release agent
Corrosion preventing	Spindles
Leaves a non-stick film	Sliding surfaces
Withstands low and high temperatures	Rubber details etc.

TECHNICAL DATA

Colour                      | Transparent

The product is H1 registered, NSF No 139633, InS No 1794481

MPI approved C15  
(All animal product except dairy)

Imported and Distributed by Oil Imports Ltd, 56 Whakatu Road, Whakatu, Hastings, 4172.

Phone: 06 871 5325, Fax: 06 870 4890, [www.totaloilsolutions.co.nz](http://www.totaloilsolutions.co.nz).

Oil Imports Ltd. is the authorised dealer of Cargo products in New Zealand.