

F-SPRAY 222

**Food Grade Penetrating Lubricant**

F-SPRAY 222 is a food-grade penetrating lubricant based on Teflon and synthetic base oils. Penetrates effectively when applied and leaves a strongly adhesive lubricating film. Protects against corrosion in aggressive environments, rejects water and also rejects dust and particles due to the "non-stick" properties in Teflon. The product is a H1 registered, food-grade lubricant recommended for all applications where a transparent, odour- and tasteless lubricant is needed. The spray can itself, is developed in a way that it enables full 360 degree functionality. This makes it possible to apply the product in all areas – even those which can be hard to reach.

Properties	Applications
Highly penetrating	Penetrating lubricant
Wide working temperature range	Chains
Rejects water/dust	Guides and other sliding surfaces
Broad range of uses	X-ray equipment
Food-grade lubricant	Rust dissolving
User-friendly	Bakery-trolleys
	Pneumatic tools
	Meat processing equipment
	etc.

TECHNICAL DATA

Colour	Transparent
Application temperature range °C	-48 to +235

MPI approved C15  
(All animal product except dairy)

Imported and Distributed by Oil Imports Ltd, 56 Whakatu Road, Whakatu, Hastings, 4172.

Phone: 06 871 5325, Fax: 06 870 4890, [www.totaloilsolutions.co.nz](http://www.totaloilsolutions.co.nz).

Oil Imports Ltd. is the authorised dealer of Cargo products in New Zealand.