VALONA MS 7023 HC





Chlorine-free neat cutting oil for heavy duty machinings.

UTILISATIONS

- VALONA MS 7023 HC is a chlorine-free neat cutting oil dedicated to both ferrous and non-ferrous metals.
- VALONA MS 7023 HC is widely used on cutting operations on hard and very hard steels (bearing steels), on special, stainless and refractory steels (NIMONIC and VASPALLOY) and on titanium alloys (aviation and medical applications). It can also be used on low carbon steels and copper alloys. Machinings lubricated: turning, screwcutting, milling, threading, tapping, sawing, deep drilling.

SPECIFICATIONS

■ VALONA MS 7023 HC is homologated by GROB-WERKE

ADVANTAGES

- Very good antiwear and extreme pressure performances:
 - increases the tool lifetime,
 - prevents ridging,
 - very good surface finish,

This product is formulated from a premium base stock and provide many advantages:

- Very little odour due to its low aromatic compound content.
- Improvement to operators health due to almost no carcinogenic compounds as polycyclic aromatic hydrocarbons present in the oil.
- Reduced oil mists and less product consumption through evaporation, due to low levels of volatility.
- Supreme product life is ensured though increased oxidation stability.
- Improved filtration ratio, due to efficient degassing of the product.
- Excellent compatibility against elastomers and paints

TYPICAL CHARACTERISTICS	METHODS	UNITS	VALONA MS 7023 HC
Appearance	-	-	Clear liquid
Colour	-	-	Yellow
Density at 15°C	ISO 3675	kg/m³	856
Kinematic viscosity at 40°C	ISO 3104	mm²/s	23
Copper corrosion	ISO 2160	-	1a
Open cup flash point	ISO 2592	°C	> 200

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS INDUSTRIE 13-07-2020 VALONA MS 7023 HC 1/1

