## WHITE PETROLEUM JELLY

Vaselin USP is a petroleum jelly of medicinal quality, a homogeneous mixture of highly refined and hydrotreated hydrocarbons, giving a gel which is almost odourless and with excellent shear strength and relatively high viscosity. Recommended for use where moisture and corrosion resistance is required and desired. Excellent for battery poles, connections and terminals. Widely employed in food processing plants and other industries with high requirements of purity and inert properties.

#### <u>Characteristics</u>

Water-resistant Relatively high viscosity High shear strength Corrosion preventing

#### **Applications**

Food processing industry Batteries and accumulator contacts Guides and tracks Joints etc.

## Technical data

NLGI grade		N/A
Colour		Whitish
Viscosity at 100 °C , mm <sup>2</sup> /s	ISO 3104	7-11
Congealing point, °C	ASTM D938	44-55
Dropping point, °C	ISO 2176	44-55
Foreign organic matter		Nil
Water		Insoluble
Acidity/alkalinity		Neutral
Product code		1500

#### SDS – Safety Data Sheet

Order from www.cargo-oil.se or contact us by phone +46 31-443311

### Standard packages

- 180 kg drum
- 50 kg drum
- 18 kg pail
  5 kg can



# CARGO OIL AB www.cargo-oil.se









