

## NEPTUNA SPEEDER 25W-40

Gasoline engine oil

### KEY DATA



✓ Leisure Boating

### SPECIFICATIONS AND APPROVALS

#### International Specifications:

API SM  
NMMA FC-W (CAT)<sup>®</sup>

#### Meets the requirements of:

✓ MERCURY

#### Suitable for:

✓ BOMBARDIER  
✓ EVINRUDE  
✓ JOHNSON  
✓ KAWASAKI  
✓ MARINER  
✓ SUZUKI  
✓ TOHATSU  
✓ YAMAHA  
✓ etc.

### APPLICATIONS

TOTAL NEPTUNA SPEEDER 25W-40 is a **mineral** lubricant developed for recent **4-stroke outboard gasoline engines** with standard and intensive use.

It is particularly recommended for **marine inboard and outboard engines** with high rpm and heavy loads.

### PERFORMANCES AND CUSTOMER BENEFITS

TOTAL NEPTUNA SPEEDER 25W-40 exhibits **excellent shear resistance**, ensuring very high oil film resistance under all conditions.

Thanks to its high viscosity, TOTAL NEPTUNA SPEEDER 25W-40 offers **exceptional engine protection**, even at high operating temperatures.

Outstanding **detergent and dispersant properties** keep the engine clean and guarantee sustained engine performance.

The association of **anti-wear and antioxidant** additives ensures extended engine lifespan.

Its **anti-rust and anti-corrosion properties** protect the engine from moisture-induced damages.

# NEPTUNA SPEEDER 25W-40

Gasoline engine oil

## PHYSICAL AND CHEMICAL CHARACTERISTICS \*

TEST	UNIT	TEST METHOD	VALUE
Kinematic Viscosity at 40 °C	mm <sup>2</sup> /s	ASTM D445	137.6
Kinematic Viscosity at 100 °C	mm <sup>2</sup> /s	ASTM D445	14.85
Viscosity Index	-	ASTM D2270	109
Flash Point	°C	ASTM D92	244
Pour Point	°C	ASTM D97	-24

\* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

## RECOMMENDATIONS FOR USE

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C.

Exposure to strong sunlight, extreme cold or high temperature variations must be avoided. All packages should be protected from bad weather conditions.

The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

## HEALTH, SAFETY AND THE ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed.

It is accessible on request from your local dealer or on the website <https://sdstotalms.total.com>.

This product should not be used for applications other than those for which it is intended. If disposing of used product, take care to protect the environment and comply with local regulations.