

HI-PERF 2T 900

2-Stroke Engine Oil

KEY DATA



Synthetic engine oil

INTERNATIONAL STANDARDS

- JASO FD
- API TC

TECHNOLOGIES

Durability Improver technology

4 Actions to maximize the durability of your bike:

- Protection against harmful piston deposits
- Protection against gear pitting and wear
- Protection against clutch slippage
- Protection against thermo-oxidative attack

Cooling Effect technology

Reduces the impact of heat dissipated by the engine and keeps your ride cool.

Fuel Economy technology

Reduces friction generated inside the engine to deliver fuel efficiency benefits.

APPLICATIONS

HI-PERF 2T 900 is a fully synthetic 2-stroke engine oil for motorcycles. It is Specially designed to bring ultimate performance under all temperatures and improved power and acceleration whether on the road or on the race track.

CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	-
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	75
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	11
OC Flash Point	°C	ASTM D92	108
Viscosity index	-	ASTM D2270	136
Pour point	°C	ASTM D97	-30
Density	kg/m ³	ASTM D97	880

*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

