

F-GREASE 132

Transparent Synthetic Lubricating Grease with PTFE

F-GREASE 132 is based on synthetic oils and PTFE. Clear Grease will fulfil all severe specifications from bearing manufacturers, industrial applications and vehicle producers. Very suitable for use where long service life is required and desired. The specific rheological properties of the lubricant will give very good low flow properties of the grease at extremely low temperatures, at the same time the high film strength and thickness will guarantee lubrication also at elevated temperatures. The type of PTFE used will adhere strongly to all surfaces lubricated and give a very low friction coefficient. F-Grease 132 is water resistant, withstands oxidation, has very good mechanical stability, is completely non-toxic and provides a very wide application temperature range.

| Properties | Applications |
|--|-------------------------------|
| Food grade grease | Food industry |
| Excellent adhesion | Tobacco industry |
| Very wide application temp. range | Pharmaceutical industry |
| Mechanically stable | Elevator screws |
| Good flow properties at low temperatures | Vehicles |
| | High temperature applications |
| | etc. |

TECHNICAL DATA

| | | Clear Grease 2 |
|---------------------------------------|----------|-------------------|
| NLGI grade | | 2 |
| Colour | | Translucent white |
| Base oil type | | Synthetic |
| Viscosity, mm ² /s, 40 °C | ISO 3104 | 80 |
| Viscosity, mm ² /s, 100 °C | | 22.7 |
| Dropping point, °C | ISO 2176 | >250 |
| Flash point, °C | ISO 2592 | >220 |
| Application temperature range, °C | | -40 to +260 |

MPI approved C15
(All animal product except dairy)

Imported and Distributed by Oil Imports Ltd, 56 Whakatu Road, Whakatu, Hastings, 4172.

Phone: 06 871 5325, Fax: 06 870 4890, www.totaloilsolutions.co.nz.

Oil Imports Ltd. is the authorised dealer of Cargo products in New Zealand.