

TRAXIUM AXLE 9 FE 75W-140

Transmission Oil

KEY DATA



INTERNATIONAL STANDARDS

- 🔥 API GL-5

MANUFACTURER APPROVALS

- 🔥 API GL-5
- 🔥 SCANIA STO 2:0 A
- 🔥 Meritor O-76M

SUITABLE FOR

- 🔥 SAE J2360

TECHNOLOGY

Life-boost technology

Your peace of mind solution.

Life-boost technology will maximize the durability of the components and parts of the driveline equipment of your vehicle.

Our products will offer the best services as your vehicle will require drastically less maintenance providing reduced Total Cost Ownership (TCO) with on top a significant extended drain interval. A solution which offers a peace of mind throughout the normal lifetime of your vehicle.



APPLICATIONS

TRAXIUM AXLE 9 FE 75W-140 is a very high performance multigrade axle oil, formulated for the most severely loaded gear applications, with fuel economy synthetic technology.

TRAXIUM AXLE 9 FE 75W-140 is recommended for manual gearboxes, rear axles, or any gear assembly requiring API GL-5 or SAE J2360 levels of performance.

TRAXIUM AXLE 9 FE 75W-140 is particularly suitable for the lubrication of rear axles of commercial vehicles from SCANIA, especially highly loaded hub-reduction and tandem axles, and latest generation axles.

PERFORMANCES & CUSTOMER BENEFITS

- Reduced fuel consumption in comparison with standard lubricants due to TOTAL's Fuel Economy technology.
- Reduced cost of maintenance: specially formulated to reach extended drain intervals recommended by the manufacturer.
- Excellent protection of axles against wear and corrosion due to extreme-pressure properties of oil.
- Excellent stability in operation due to high viscosity index.
- High compatibility with oil filters due to antifoam properties.

CHARACTERISTICS *

TEST	UNIT	TEST METHOD	RESULT
Density at 15°C	kg/m3	DIN 51757 D	865
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	180
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	25
Viscosity index	-	ASTM D2270	180
Pour point	°C	ASTM D97	-48

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

