

Isovoltine P2

Inhibited mineral insulating fluid

APPLICATIONS

- **Isovoltine P2** oil is an inhibited mineral oil for transformers, switchgears, circuit breakers, welding set, and all high voltage electrical equipment.

ADVANTAGES

- Excellent resistivity, power factor and dielectric strength.
- Low viscosity for effective cooling
- Outstanding oxidation resistance providing long life.
- Very low pour point.
- No impurities such as dissolved gas, water or suspended solids.
- Does not contain DBDS.
- Does not contain PCB.

SPECIFICATIONS

- IEC 60296:2012 – Inhibited
- BS 148 Class IA
- KS C 2301
- JIS C 2320 Class 1, Class IA, IIA
- Suitable for the equipment requiring ASTM D 3487 Type II fluid

APPROVALS



For additional information, contact your local Totalenergies Lubricants representative or visit our web site: <https://lubricants.totalenergies.com>

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded from <https://sdstotalms.total.com>

TYPICAL CHARACTERISTICS

Properties	Units	Standards	Isovoltine P2
Density at 20°C	gc/m ³	ISO 3675	0.825
Viscosity at 40°C	mm ² /s	ISO 3104	7.70
Flash point (Pensky Martens, Closed Cup)	°C	ISO 2719	145
Pour point	°C	ISO 3016	-45
Acidity	mg KOH/g	IEC 62021-1	< 0.01
Water content	ppm	IEC 60814	17
Antioxidant additives	%wt	IEC 60666	< 0.08
Corrosive sulfur	-	DIN 51353	Non corrosive
Breakdown voltage	kV	IEC 60156	> 30
DDF at 90°C	%	IEC 60247	< 0.001
Oxydation stability, 332 h	%wt	IEC 611256C	< 0.01
- Sludge	mg KOH/g		0.12
- Total Acidity			



For additional information, contact your local Totalenergies Lubricants representative or visit our web site: <https://lubricants.totalenergies.com>

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded from <https://sdstotalms.total.com>

TotalEnergies Lubrifiants

SA 552 006 454 RCS Nanterre - France