

## ASP LITHPLEX EP 0 GREASE

<u>TEST</u>	<u>ASTM METHOD</u>	
NLGI		0
Lithium Soap, % mass	-	4.7
Colour	-	Dark Brown
Texture	-	Smooth
Penetration at 25°C:		
Worked 60 strokes	D.217	370
Dropping Point °C	D.2265	170
Oxidation Stability -		
Pressure Drop at 100 hr, kPa	D.942	30
Rust Test	D.1743	Pass
Timken, OK Load, kg	D.2509	23
4-Ball EP Weld Point, kgf	D.2596	290
4-Ball Wear Scar, mm	D.2266	0.48
Base Oil Specification -		
Viscosity, cSt at 40°C	D.445	190
Operating Temperature Range °C		-20°C to 130°C

**Supplier Product Code:** 60202

**AMTEX**  
HIGH PERFORMANCE OILS

Effective: September 2013  
Cancels: September 2004

Imported and distributed by **Oil Imports Ltd**  
[www.totaloilsolutions.co.nz](http://www.totaloilsolutions.co.nz)



**Oil Imports Ltd**  
56 Whakatu Road, Whakatu, Hastings 4172.  
PO Box 13 049, Mahora, Hastings 4155.  
Phone: 06 871 5325 Fax: 06 870 4890.  
Email: [office@oilimports.co.nz](mailto:office@oilimports.co.nz)  
[www.totaloilsolutions.co.nz](http://www.totaloilsolutions.co.nz)