



SAFETY DATA SHEET

according to SS 586

SDS # : 084306

RUBIA FLEET HD 200 SAE 40

Issuing date: 2015-06-30

Revision date: 2018-07-19

Version 1.04

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	RUBIA FLEET HD 200 SAE 40
Number	BTL
Substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Motor oil.
------------------------	------------

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL OIL ASIA PACIFIC PTE LTD 331 North Bridge Road #23-01 Odeon Towers Singapore 188720 Tel: +65 6879 2200 Fax: +65 6879 2203
Importer	OIL INTEL LIMITED 56 Whakatu Road, Whakatu Hastings 4172 NEW ZEALAND Phone: +64 (06) 871 53 25 Fax: +64 (06) 870 48 90

For further information, please contact:

Contact Point	HSE
E-mail Address	ms.ap-sds@total.com

1.4. Emergency telephone number

New Zealand Poisons Information Centre: 0800 764 766
New Zealand: +64 9801 0034.

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

This product is not classified as hazardous according to Singapore Standard SS 586 on the Hazard Communication for Hazardous Chemicals and Dangerous Goods

Label elements

This product is not classified as hazardous according to Singapore Standard SS 586 on the Hazard Communication for Hazardous Chemicals and Dangerous Goods



SAFETY DATA SHEET

according to SS 586

SDS # : 084306

RUBIA FLEET HD 200 SAE 40

Issuing date: 2015-06-30

Revision date: 2018-07-19

Version 1.04

Other hazards which do not result in classification

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	EC-No	Weight %
Branched alkylphenol and calcium branched alkylphenol	^	-	0.1-<0.25

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	Not classified.
Eye contact	Not classified.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

Version SGPE



SAFETY DATA SHEET

according to SS 586

SDS # : 084306

RUBIA FLEET HD 200 SAE 40

Issuing date: 2015-06-30

Revision date: 2018-07-19

Version 1.04

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

5.3. Advice for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Personal Protective Equipment See Section 8 for more detail.

Version SGPE



SAFETY DATA SHEET

according to SS 586

SDS # : 084306

RUBIA FLEET HD 200 SAE 40

Issuing date: 2015-06-30

Revision date: 2018-07-19

Version 1.04

Waste treatment See section 13.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling	When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.
Prevention of fire and explosion	Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and at the end of workday. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions	Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.
Materials to Avoid	Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits	Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m ³ , NIOSH (REL) TWA 5 mg/m ³ , STEL 10 mg/m ³ , ACGIH (TLV) TWA 5 mg/m ³ (highly refined).
------------------------	--

Legend See section 16

Version SGPE



SAFETY DATA SHEET

according to SS 586

SDS # : 084306

RUBIA FLEET HD 200 SAE 40

Issuing date: 2015-06-30

Revision date: 2018-07-19

Version 1.04

8.2. Exposure controls

Occupational Exposure Controls

Engineering Measures

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Personal Protective Equipment

General Information

If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

Eye Protection

If splashes are likely to occur, wear: Safety glasses with side-shields.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.

Hand Protection

Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.

Environmental exposure controls

General Information

The product should not be allowed to enter drains, water courses or the soil.

9. PHYSICAL AND CHEMICAL PROPERTIES

General Information

Color	yellow To brown
Physical State @20°C	liquid
Odor	Characteristic
Odor Threshold	No information available

Important health safety and environmental information

Version SGPE



SAFETY DATA SHEET

according to SS 586

SDS # : 084306

RUBIA FLEET HD 200 SAE 40

Issuing date: 2015-06-30

Revision date: 2018-07-19

Version 1.04

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		Not applicable	
Melting point/range		Not applicable	
Boiling point/boiling range		No information available	
Flash point	256 °C 493 °F		ASTM D92 ASTM D92.
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Relative density	0.8892	@ 15 °C	ASTM D4052
Density	889.2 kg/m ³	@ 15 °C	ASTM D4052
Water solubility		Insoluble	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		No information available	
Decomposition temperature		No information available	
Viscosity, kinematic	137.2 mm ² /s 14.19 mm ² /s	@ 40 °C @ 100 °C	ASTM D445 ASTM D445
Explosive properties	Not explosive		
Oxidizing Properties	No information available		
Possibility of hazardous reactions	None under normal processing		

Other information

Freezing Point		No information available
Pour point	-36 °C	ASTM D97

10. STABILITY AND REACTIVITY

10.1. Reactivity

General Information No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Version SGPE



SAFETY DATA SHEET

according to SS 586

SDS # : 084306

RUBIA FLEET HD 200 SAE 40

Issuing date: 2015-06-30

Revision date: 2018-07-19

Version 1.04

Hazardous Reactions None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

10.5. Incompatible Materials

Materials to Avoid Strong oxidizing agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Information on likely routes of exposure

Principle Routes of Exposure Skin contact, Eye contact, Inhalation, Ingestion.

Skin contact	Not classified.
Eye contact	Not classified.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity - Product Information

Oral	Not classified.
Dermal	Not classified.
Inhalation	Not classified.

Acute toxicity - Component Information

No information available

Version SGPE



SAFETY DATA SHEET

according to SS 586

SDS # : 084306

RUBIA FLEET HD 200 SAE 40

Issuing date: 2015-06-30

Revision date: 2018-07-19

Version 1.04

Skin corrosion/irritation	Not classified.
Serious eye damage/eye irritation	Not classified.
Sensitization	Not classified as a sensitizer.
Germ Cell Mutagenicity	This product is not classified as mutagenic.
Carcinogenicity	This product is not classified carcinogenic. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

Reproductive toxicity Not classified. Contains a presumed human reproductive toxicant substance.

Chemical Name	European Union
Branched alkylphenol and calcium branched alkylphenol ^	Repr. 1B (H360)

STOT-single exposure	Not classified.
STOT - repeated exposure	Not classified.
Aspiration Hazard	Not classified.
Other adverse effects	Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

12. ECOLOGICAL INFORMATION

12.1. Toxicity

Not Classified.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

No information available.

Version SGPE



SAFETY DATA SHEET

according to SS 586

SDS # : 084306

RUBIA FLEET HD 200 SAE 40

Issuing date: 2015-06-30

Revision date: 2018-07-19

Version 1.04

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

No information available.

Effects on terrestrial organisms

No information available.

12.2. Persistence and degradability

General Information No information available.

12.3. Bioaccumulative potential

Product Information No information available.

logPow No information available
Component Information No information available.

12.4. Mobility in soil

Soil Given its physical and chemical characteristics, the product generally shows low soil mobility.

Air Loss by evaporation is limited.

Water The product is insoluble and floats on water.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

12.6. Other adverse effects

General Information No information available.

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Version SGPE



SAFETY DATA SHEET

according to SS 586

SDS # : 084306

RUBIA FLEET HD 200 SAE 40

Issuing date: 2015-06-30

Revision date: 2018-07-19

Version 1.04

Waste Disposal Methods	Should not be released into the environment. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
Disposal Precautions	Refer to section 8 for safety and protective measures for disposal personnel.

14. TRANSPORT INFORMATION

<u>ADR/RID</u>	Not regulated
<u>IMDG/IMO</u>	Not regulated
<u>ICAO/IATA</u>	Not regulated

15. REGULATORY INFORMATION

National regulatory information

Singapore

Applicable National Regulation:
Workplace Safety and Health (General Provision) Regulations

New Zealand Regulatory Information:

HSNO Approval Number HSR002605
HSNO Group Standard Lubricants (Low Hazard) Group Standard 2006

HSNO Classification 6.3 - SKIN IRRITATION - Category B
6.4 - EYE IRRITATION - Category A (Irritant)
9.1 - AQUATIC ECOTOXICITY - Category D

Regulation according to other foreign laws:

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations

16. OTHER INFORMATION

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals



SAFETY DATA SHEET

according to SS 586

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration NOEL = No Observed Effect Level OECD = Organization for Economic Co-operation and Development OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

Legend Section 8

TWA: Time Weight Average

STEL: Short Time Exposure Limit

PEL: Permissible exposure limit

REL: Recommended exposure limit

TLV: Threshold Limit Values

+	Sensitizer	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

Revision Date: 2018-07-19

Revision Note *** Indicates updated section.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet