



FLUIDMATIC MV

Automatic Transmission Fluid

PERFORMANCES LEVELS

Meets the requirements

- ✓ Aisin Warner JWS 3309 / 3317
- ✓ Chrysler/Dodge/Jeep ATF +3 / +4
- ✓ Hyundai-Kia SP-II/III
- ✓ JASO 1A (M315)
- ✓ Toyota D-II / T / T-III / T-IV

Suitable for

- ✓ Ford Mercon / Mercon V / WSS-M2C922-A1
- ✓ GM Dexron Type A Suffix A/II/III/IIIG/IIIH
- ✓ MAN 339 Type A
- ✓ Mercedes-Benz MB 236.3/9/10/11/91
- ✓ ZF TE-ML 11A/11B
- ✓ Audi/Volkswagen : G 052 025 (A2) / G 052 162 (-A1, -A2) / G 052 055 / G 052 990 (A2) / G 055 025 (A2) / G US 000 162
- ✓ BMW/Mini : P/N 81229400272/275, 81229407858/859, 83220024249/359, 83220026922, 83220402413, 83220403248, 83227542290, 83229407765, 83229407807
- ✓ Ford : P/N XT-2-QDX [M], XT-2-QSM [Syn], XT-5-QM ou -DM [V], XT-8-QAW [Premium], XT-9-QMM5 [FNR5]
- ✓ GM : P/N 1940700, 1940767, 21005966, 22717466, 88900925, 9986195
- ✓ Isuzu : P/N 08200-9001
- ✓ Jaguar : JLM 20238, JLM 20292, JLM 21044
- ✓ Mazda : P/N XT-9-QMM5
- ✓ Porsche : P/N 000 043 204 41, 000 043 205 09, 000 043 205 28, 999 917 547 00 (A2)
- ✓ PSA : P/N Z 000169756
- ✓ Ssang Yong : DSIH 5M-66
- ✓ Subaru : P/N K0140Y0700
- ✓ VCE : 1273,41
- ✓ Volvo : P/N 1161521 / 1161540 / 1161640

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

FLUIDMATIC MV

Update: 07/2017



APPLICATIONS

- FLUIDMATIC MV is a premium automatic transmission fluid based on an advanced synthetic technology allowing very high performance needed for the demanding requirements of passenger cars automatic gearboxes.
- This Lubricant can be used in a broad range of automatic transmission standards (Asian, European, American...). It's particularly suitable for 4 and 5 speeds automatic transmissions.
- FLUIDMATIC MV provides outstanding oxidation and thermal stability resulting in lower deposit and harmful acidic by-product formation. Further, it helps to improve overall transmission durability and cleanliness

CUSTOMER BENEFITS

- **Excellent friction and anti-shudder performances:** FLUIDMATIC MV has been formulated with selected viscosity modifiers which provide excellent friction characteristics. These improve driver's comfort with smooth and efficient shifting without shudder.
- **Excellent viscosity stability in operation:** FLUIDMATIC MV has been properly formulated to remain shear stable over time providing extended life time of the fluid.
- **Excellent durability thanks to its high quality base oils and additives.**
- **Superior protection against wear, rust and corrosion**
- **Very good thermal and oxidation stability**
- **Foaming prevention**
- **Excellent parts material compatibility**

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

FLUIDMATIC MV

Update: 07/2017



PHYSICAL AND CHEMICAL CHARACTERISTICS

FLUIDMATIC MV	Unit	Method	Value
Colour	-	ASTM D1500	Red
Density at 15°C	kg/m ³	ASTM D4052	847
Kinematic Viscosity at 40 °C	mm ² /s	ASTM D445	36.04
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	6,808
Brookfield Viscosity at -40°C	cP	ASTM D2983	19800
Viscosity Index	-	ASTM D2270	154
Pour Point	°C	ASTM D97	-42
Flash Point	°C	ASTM D92	208

**The features mentioned above are average values obtained with some variability in production and do not constitute a specification.*

RECOMMENDATIONS FOR USE

Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.

The product should not be stored at a temperature above 60 °C while avoiding exposure to strong sunlight, extreme cold or high temperature variations.

All packages should be protected from bad weather conditions. Otherwise, the drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information, this product does not cause adverse health effects when used in the intended application and the recommendations provided in the Safety Data Sheet (MSDS) are followed. The information is accessible on request from your local dealer or on the website www.quickfds.com.

This product should not be used for applications other than those for which it is intended.

If disposing of used product, take care to protect the environment and comply with local regulations.

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

FLUIDMATIC MV

Update: 07/2017



This lubricant does not cause adverse health effects when used in the intended application. A safety datasheet, is accessible on request from your local dealer.