

NEVASTANE CHAIN OIL XT



Food industry



High-temperature synthetic chain oil, suitable for incidental food contact.

APPLICATIONS

- **NEVASTANE CHAIN OIL XT** is a high performance chain oil specially designed for the lubrication of any control, drive and transport chains subject to high temperatures and loads in the food industries: bakeries, slaughterhouses, beverage industries, etc...
- **NEVASTANE CHAIN OIL XT** is suitable for temperature up to 260 °C.

SPECIFICATIONS

- **NEVASTANE CHAIN OIL XT** formulation complies with FDA, chapter 21 CFR, 178.3570.
- **NEVASTANE CHAIN OIL XT** is **NSF H1** registered: No 144427.
- **NEVASTANE CHAIN OIL XT** is a biostable product, it does not promote the development of bacteria and mould.

ADVANTAGES

- **NEVASTANE CHAIN OIL XT** is recommended for use where incidental contact with food may occur. Using maintenance lubricants which have been registered H1 with NSF minimizes your critical control points as required by HACCP.
- Formulation based on high performance complex neopolyol esters.
- Exceptional resistance to high temperatures and adhesion properties.
- Low evaporation and high flash point.
- Reduction in oil consumption and significant extensions of lubrication intervals.

TYPICAL CHARACTERISTICS	METHODS	UNITS	NEVASTANE CHAIN OIL XT
Appearance	ISO 4630	-	Clear and bright
Density @ 20°C	ISO 12185	-	962
Kinematic viscosity @ 40 °C	ISO 3104	mm ² /s	220
Kinematic viscosity @ 100 °C	ISO 3104	mm ² /s	18.5
Viscosity index	ISO 2909	-	95
Flash point OC	ISO 2592	°C	296
Pour point	ISO 3016	°C	- 21
Acid number	ISO 6619	mg KOH/g	0.3

Above characteristics are mean values given as an information.

Recommendations: - Store between -10°C and +50°C
- Shelf life: 3 years from date of manufacture (unopened)

TOTAL LUBRIFIANTS
INDUSTRIE

20-06-2017 (supersedes 18-04-2016)
NEVASTANE CHAIN OIL XT
1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.quick-fds.com.