



SAFETY DATA SHEET
According to HSNO Approved Code of Practice 8-1 09-06

SDS #: 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

Product identifier

Product name TRANSMISSION AXLE 8 80W-90

Other means of identification

Number DHE
Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Transmission fluid.

Details of the supplier of the safety data sheet

Supplier TOTAL OIL ASIA PACIFIC PTE LTD
182 Cecil Street
#27-01 Frasers Tower
Singapore 069547
Tel: +65 6879 2200
Fax: +65 6879 2203

Importer Oil Intel Limited
56 Whakatu Road, Whakatu
Hastings 4172
NEW ZEALAND
Phone: +64 (06) 871 53 25
Fax: +64 (06) 870 48 90

For further information, please contact:

Contact Point HSE
E-mail Address ms.ap-sds@total.com

Emergency telephone

New Zealand: +64 9 929 1483
Asia-Pacific: +65 3158 1074
New Zealand Poisons Information Centre: 0800 764 766

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Not classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001

Version ZGHS



SDS # : 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

GHS Label elements, including precautionary statementsSignal word **None****Hazard Statements**

None

Other hazards which do not result in classification

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.
Environmental properties The product may form an oil film on the water surface that may stop the oxygen exchange.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Chemical nature** Mineral oil of petroleum origin.

| Chemical Name | CAS-No | EC-No | Weight % |
|---|--------------|-----------|-----------|
| Polysulfides, di-tert-Bu | 68937-96-2 | 273-103-3 | 3-<5 |
| Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14-tert-alkyl | ^ | 931-384-6 | 1-<2.5 |
| Reaction products of alcohols, C14-18,C18 unsat,,esterified with phosphorus pentoxide and salted with amines,C12-14,-tert-alkyl | 1471315-74-8 | 939-591-3 | 1-<2.5 |
| 2-ethylhexyl 10-ethyl-4-[[2-[(2-ethylhexyl)oxy]-2-oxoethyl]thio]-7-oxo-8-oxa-3,5-dithia-4-phosphatetradecanoate 4-oxide | 83547-95-9 | 280-479-2 | 0.25-<1 |
| Reaction product of 1,3,4-thiadiazolidine-2,5-dithione,formaldehyde and phenol,heptyl derivs. | ^ | 939-460-0 | 0.1-<0.25 |

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346**4. FIRST AID MEASURES****Description of necessary first-aid measures**

Version ZGHS



SDS # : 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

| | |
|-----------------------------------|--|
| General advice | IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE. |
| Eye contact | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. |
| Skin contact | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. Take victim immediately to hospital. |
| Inhalation | Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. |
| Ingestion | Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately. |
| Protection of First-aiders | First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. |

Most important symptoms/effects, acute and delayed

| | |
|---------------------|---|
| Skin contact | Not classified based on available data. May produce an allergic reaction. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent. |
| Eye contact | Not classified based on available data. |
| Inhalation | Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system. |
| Ingestion | Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |

Indication of immediate medical attention and special treatment needed, if necessary

| | |
|---------------------------|------------------------|
| Notes to physician | Treat symptomatically. |
|---------------------------|------------------------|

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion

Version ZGHS



SDS # : 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S, Phosphorous oxides, Nitrogen oxides (NO_x), Mercaptans, Silicon dioxide.

Advice for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information

Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Environmental precautions

General Information Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.

Methods for cleaning up Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

Other information

Personal Protective Equipment See Section 8 for more detail.

Waste treatment See section 13.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Version ZGHS



SDS # : 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

| | |
|--|--|
| Prevention of fire and explosion | Take precautionary measures against static discharges. |
| Hygiene measures | Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. |
| <u>Conditions for safe storage, including any incompatibilities</u> | |
| Technical measures/Storage conditions | Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture. |
| Materials to Avoid | Strong oxidizing agents. |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

| | |
|------------------------|--|
| Exposure limits | Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m ³ , NIOSH (REL) TWA 5 mg/m ³ , STEL 10 mg/m ³ , ACGIH (TLV) TWA 5 mg/m ³ (highly refined). |
|------------------------|--|

Appropriate engineering controls

| | |
|-----------------------------|---|
| Engineering Measures | Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment. |
|-----------------------------|---|

Individual protection measures, such as personal protective equipment (PPE)

Personal Protective Equipment

| | |
|----------------------------|--|
| General Information | Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers. |
|----------------------------|--|

Version ZGHS



SDS # : 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

| | |
|---------------------------------|--|
| Respiratory protection | None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387): Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses. |
| Eye Protection | If splashes are likely to occur, wear: Safety glasses with side-shields. EN 166. |
| Skin and body protection | Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type 4/6. |
| Hand Protection | Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. |

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | | | |
|------------------------------------|-----------------------------|--------------------------|--|
| Appearance | | limpid | |
| Color | | brown | |
| Physical State @20°C | | liquid | |
| Odor | | Characteristic | |
| Odor Threshold | | No information available | |
| Property | Values | Remarks | Method |
| pH | | Not applicable | |
| Melting point/range | | Not applicable | |
| Boiling point/boiling range | | No information available | |
| Flash point | > 160 °C > 320 °F | | Cleveland Open Cup (COC) Cleveland Open Cup (COC) |
| Evaporation rate | | No information available | |
| Flammability Limits in Air | | | |
| upper | | No information available | |
| Lower | | No information available | |
| Vapor Pressure | | No information available | |
| Vapor density | | No information available | |
| Relative density | 0.890 - 0.910 | @ 15 °C | ISO 12185 |
| Density | 890 - 910 kg/m ³ | @ 15 °C | ISO 12185 |

Version ZGHS



SDS # : 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

| | | | |
|---|------------------------------|---------|----------|
| Water solubility | Insoluble | | |
| Solubility in other solvents | No information available | | |
| logPow | No information available | | |
| Autoignition temperature | No information available | | |
| Decomposition temperature | No information available | | |
| Viscosity, kinematic | 125 - 145 mm ² /s | @ 40 °C | ISO 3104 |
| Explosive properties | Not explosive | | |
| Oxidizing Properties | Not applicable | | |
| Possibility of hazardous reactions | None under normal processing | | |

9.2. Other information

Freezing Point No information available

10. STABILITY AND REACTIVITY

| | |
|--|--|
| <u>Reactivity</u> | None under normal processing. |
| <u>Chemical stability</u> | Stable under recommended storage conditions. |
| <u>Possibility of hazardous reactions</u> | No dangerous reaction known under conditions of normal use. |
| <u>Conditions to avoid</u> | Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks. |
| <u>Incompatible materials</u> | Strong oxidizing agents. |
| <u>Hazardous Decomposition Products</u> | Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Combustion products include sulphur oxides (SO ₂ and SO ₃) and Hydrogen sulphide H ₂ S, Phosphorous oxides, Nitrogen oxides (NO _x), Mercaptans, Silicon dioxide. |

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| | |
|---------------------|---|
| Inhalation | Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system. |
| Ingestion | Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Skin contact | Not classified based on available data. May produce an allergic reaction. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent. |
| Eye contact | Not classified based on available data. |

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Version ZGHS



SDS # : 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Acute toxicity - Product Information**

| | |
|---|---|
| Oral | Not classified based on available data. |
| ATEmix (oral) | 53,025.00 mg/kg |
| 0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity | |
| Dermal | Not classified based on available data. |
| ATEmix (dermal) | 31,945.00 mg/kg |
| 0 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity | |
| Inhalation | Not classified based on available data |
| ATEmix (inhalation-gas) | > 20,000.00 ppm |
| 14.585 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas) | |
| ATEmix (inhalation-vapor) | 882.80 mg/l |
| 12.595 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor) | |
| ATEmix (inhalation-dust/mist) | 40.20 mg/l |
| 1.495 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist) | |

Acute toxicity - Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|---|---|------------------------------------|-----------------|
| Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl ^ | LD50 2000 mg/kg bw (Rat - OECD TG 401) | | - |
| Reaction products of alcohols, C14-18,C18 unsat, esterified with phosphorus pentoxide and salted with amines, C12-14, -tert-alkyl 1471315-74-8 | LD50 > 2000 mg/kg (Rat -Female - OECD420) | LD50 > 2000 mg/kg (Rat - OECD 402) | |
| 2-ethylhexyl 10-ethyl-4-[[2-[(2-ethylhexyl)oxy]-2-oxoethyl]thio]-7-oxo-8-oxa-3,5-dithia-4-phosphatetradecanoate 4-oxide 83547-95-9 | LD50 3313 mg/kg (Rat) | LD50 > 2000 mg/kg (Rabbit) | |
| Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, for maldehyde and phenol, heptyl derivs. ^ | LD50 >2000 mg/kg (Rat) | LD50 >2000 mg/kg (Rat - OECD 402) | |

Skin corrosion/irritation Not classified based on available data.**Serious eye damage/eye irritation** Not classified based on available data. The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, classification is not required.

Version ZGHS



SDS # : 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

| | |
|------------------------------------|--|
| Sensitization | Not classified based on available data. Contains sensitizer(s). May produce an allergic reaction. The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, classification is not required. |
| Carcinogenicity | Not classified based on available data. |
| Germ Cell Mutagenicity | Not classified based on available data |
| Reproductive toxicity | Not classified based on available data. |
| Target Organ Effects (STOT) | None known |
| STOT - single exposure | Not classified based on available data |
| STOT - repeated exposure | Not classified based on available data |
| Aspiration hazard | Not classified based on available data. |
| Other adverse effects | Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing). |

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Not classified based on available data.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

| Chemical Name | Toxicity to algae | Toxicity to daphnia and other aquatic invertebrates | Toxicity to fish | Toxicity to microorganisms |
|--|--|---|---|----------------------------|
| Polysulfides, di-tert-Bu 68937-96-2 | EC50 (72h) > 100 mg/l (Alga) | EC50 (48h) 63 mg/l (Daphnia magna) | | |
| Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl ^ | EL50 (96h) > 15 mg (Selenastrum capricornutum - OECD 201) EC50 (96h) 6.4 mg/l (Pseudokirchnerella subcapitata - OECD 201) EC50 (96h) 15 mg/l (Pseudokirchnerella subcapitata - OECD 201) EC50 (96h) 6.4 mg/L (Selenastrum | EL50 (48h) ca. 91.4 mg/l (Daphnia magna - OECD 202) | LL50 (96h) ca. 24 mg/l (Oncorhynchus mykiss - OECD 203) | |

Version ZGHS



SDS # : 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

| | | | | |
|--|---|---|--|--|
| | capricornutum- OECD TG 201) (ECHA CHEM) | | | |
| Reaction products of alcohols, C14-18,C18 unsat.,esterified with phosphorus pentoxide and salted with amines,C12-14,-tert-alkyl 1471315-74-8 | EL50 (72h) 2.4 mg/l (Pseudokirchnerella subcapitata - static - OECD201) | EL50(48h) 91 mg/l (Daphnia magna - static - OECD 202) | | |
| 2-ethylhexyl 10-ethyl-4-[[2-[(2-ethylhexyl)oxy]-2-oxoethyl]thio]-7-oxo-8-oxa-3,5-dithia-4-phosphatetradecanoate 4-oxide 83547-95-9 | EC50 (72h) 3.1 mg/l (Algae) | EC50 (48h) 12.5 mg/l (Daphnia magna) | LC50 (96h) 4.3 mg/l (Fish) | |
| Reaction product of 1,3,4-thiadiazolidine-2,5-dithione,formaldehyde and phenol,heptyl derivs. ^ | EC50(72h) 25 mg/l (Pseudokirchnerella subcapitata) | LE50(48h) 75 mg/l (Daphnia magna) | LL50 (96h) 26 mg/l (Oncorhynchus mykiss) | |

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

| Chemical Name | Toxicity to algae | Toxicity to daphnia and other aquatic invertebrates | Toxicity to fish | Toxicity to microorganisms |
|--|--|---|------------------|--|
| Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl ^ | NOEC (96h) 1.7 mg/l (Pseudokirchnerella subcapitata - OECD 201) par NOEC (96h) 3.3 mg/l (Pseudokirchnerella subcapitata - OECD 201) | EL50 (21d) 0.91 mg/l (Daphnia magna - OECD 211) NOEL (21d) 0.12 mg/l (Daphnia magna - OECD 211) EL50 (21d) 0.66 mg/l (Daphnia magna - OECD 211) | - | EC50 (3h) ca. 2433 mg/L (Activated Sludge, domestic - OECD TG 209) (ECHA CHEM) |
| Reaction products of alcohols, C14-18,C18 unsat.,esterified with phosphorus pentoxide and salted with amines,C12-14,-tert-alkyl 1471315-74-8 | NOELR (72h) 1 mg/l (Pseudokirchnerella subcapitata - static - OECD 201) | | | |
| Reaction product of 1,3,4-thiadiazolidine-2,5-dithione,formaldehyde and phenol,heptyl derivs. ^ | | NOEC(21d) 0.12 mg/l (Daphnia magna) | | |

Effects on terrestrial organisms No information available.**Persistence and degradability**

Version ZGHS



SDS # : 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

No information available.

Bioaccumulative potential**Product Information**

No information available.

logPow

No information available

Component Information

| Chemical Name | log Pow |
|--|---|
| Polysulfides, di-tert-Bu - 68937-96-2 | 6 |
| Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl - ^ | < 0.30 to >7.10 (OECD TG 117) (ECHA CHEM) |
| Reaction products of alcohols, C14-18,C18 unsat.,esterified with phosphorus pentoxide and salted with amines,C12-14,-tert-alkyl - 1471315-74-8 | 5.7 |

Mobility**Soil**

Given its physical and chemical characteristics, the product generally shows low soil mobility.

Air

Loss by evaporation is limited.

Water

The product is insoluble and floats on water.

Other adverse effects**General Information**

No information available.

13. DISPOSAL CONSIDERATIONS**Waste from Residues / Unused Products**

Should not be released into the environment. Do not empty into drains. Dispose of in accordance with all applicable national environmental laws and regulations. Where possible recycling is preferred to disposal or incineration.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Other information

Refer to section 8 for safety and protective measures for disposal personnel.

14. TRANSPORT INFORMATION**ADR/RID**

Not regulated

IMDG/IMO

Not regulated

ICAO/IATA

Not regulated

Version ZGHS



SDS # : 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

15. REGULATORY INFORMATION

International Inventories

All the substances contained in this product are listed or exempted from listing in the following inventories:

Philippines (PICCS)
 U.S.A. (TSCA)
 Australia (AICS)
 Canada (DSL/NDSL)
 China (IECSC)
 New Zealand (NZIoC)
 Korea (KECL)

National regulatory information

New Zealand

- See section 8 for national exposure control parameters
- This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO)

New Zealand HSNO approval code or group standard

HSR002605, Lubricants (Low Hazard)

This SDS may not cover all of the controls relevant for this substance or mixture. The Environmental Protection Authority of New Zealand (EPA) 'User Guide to the HSNO Controls' should be consulted for a comprehensive list of controls and reference to the regulations

16. OTHER INFORMATION

Issuing date: 2018-12-28
Revision Date: 2019-05-03
Revision Note No information available

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

Legend:

Section 8



SDS # : 083163

TRANSMISSION AXLE 8 80W-90

Issuing date: 2018-12-28

Revision Date: 2019-05-03

Version 1.01

| | | | |
|----------|---------------------------|------|-----------------------|
| Ceiling: | Maximum limit value | TWA: | Time weighted average |
| STEL: | Short term exposure limit | * | Skin designation |
| + | Sensitizer | C | Carcinogen |

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet